



Stroke-Dependent Dead Zones (RF Model)
 Stroke Length: Dead Zones
 254-9144 mm (10-360 in.) 94 mm (3.7 in.)

C	01/13/00	KLP	4246	DELETED SECTION OF RIGID PIPE
B	01/13/00	LJH	3972	ADDED SECTION OF RIGID PIPE
A	10/29/99	KLP	3862	RELEASE TO PRODUCTION
REV.	DATE	BY	ECO #	DESCRIPTION

UNLESS OTHERWISE SPECIFIED

2X ± .015
 1X ± .010
 3X ± .010
 4X ± .010
 5X ± .010
 6X ± .010
 7X ± .010
 8X ± .010
 9X ± .010
 10X ± .010

REMOVE BARRIERS AND SHOW
 DIMENSIONS AND DIMENSIONS
 FROM THE CENTERLINE
 PLATING OR CONVERSION CENTER
 DIMENSIONS ARE TO
 THE CENTERLINE

10° FULL TOLERANCE

NO NET DRAWING	NO NET DRAWING	NO NET DRAWING	NO NET DRAWING
1 OF 1	1 OF 1	1 OF 1	1 OF 1
REV C	REV C	REV C	REV C

MTS
 SYSTEMS CORPORATION
 SENSORS DIVISION
 11000 W. TEMPO 3 RD
 TEMPO, OHIO 43081-9900
 PHONE: 614-890-7200
 FAX: 614-890-7201
 WWW: WWW.MTS-CORP.COM